



Victoria Queen™ w/ Classic Base

Page 15

TOP:

Top design	Four section, round corners, 3 layer foam, electrically-adjusted back and knees
Top features	Tapered backrest, no accessory holes, (one size), does not lie flat for massage
Vinyl - UltraLeather - only	100% polyurethane surface with 100% reinforced Rayon backing
Foam	Urethane polymer, no CFC's, 3/4" firm bottm layer, 1-3/4" medium density middle layer
Polyester batting	1/2" fluffy polyester dacron top layer
Overall Size - knees up	66" long, 44.5" to top of backrest, 25" wide (32" wide including armrests)
Overall Size - knees flat	58" long, 51.5" to top of backrest, 25" wide (32" wide including armrests)
Maximum width	77" with both side arms swung out
Lift and tilt angles	Back = 45... to 70..., knees = 0... to 30..., foot = 0" to 6.5" from cabinet top
Mechanical movement	Back slides forward as knee section rises, foot adjusts manually
Top lift mechanism	24 VDC Motor-Linak LA31, permanent magnet motor, built-in end limit switches, UL listed
Control box-Linak CB09	110 volt AC in, 24 volt DC out, UL listed

INCLUDED ACCESSORIES:

Salon headrest	6" x 15" x 2.5" thick pad with 6" x 8.5" x 3" thick rounded, adjustable pillow
Swing-out side arms (self-locking)	6" x 26" x 2.5" thick
Padded heel rest	3" x 14" x 2.5" thick
Upholstered tub cover	14" x 15-1/4" x 2-3/4" thick, covers foot tub opening

TOP OPTIONS:

Monogrammed corners	Initials, words or design. Choice of fonts.
Hand control, 2 buttons	2 buttons for back:, 2 for foot, 2 for base. Cord reaches either end, UL listed
T'Salta Manicure arms	2 pull out trays, one flat for polishing, one with an inset bowl for soaking
Discharge Pump	For sink drainage: water activated, manual on/off override switch

BASE:

Base design	Fixed height, hardwood cabinet, storage area
Cabinet materials	Maple and birch
Size - wooden cabinet	20" x 51"
Sliding cabinet doors	Two at 19.5" x 14" high
Inner cabinet dimensions	18" x 39" x 14" high
Power requirements	110 volt 10 amp breaker is sufficient, GFCI outlet recommended
Accessory outlets	2 - 110 volt outlets, UL listed
Foot Switch - 4 pedals	(2) Knees up and down, (2) air pump on or off
Water heater	None
Air jets for whirlpool action	110 volt .5 amp diaphragm pump - feeds to 12 small holes in foot tub bottom
Air pump	Uses 24 watts at 2 PSI, has safety secondary relay, UL listed
Foot tub	16" x 14" x 12" deep, ABS plastic - recommend 2.5 gallon per use
Temperature gauge	Digital read-out, battery powered, UL listed
Tub overflow drain	Limits water height to 5" from bottom. Feeds into regular drain.
Drain Size	1.5" diameter drain connects to floor drain hose
Water hook-ups	Two hose bibs (standard 3/4" washing machine size)
Height	Fixed 24"

BASE OPTIONS:

Base finish choices	Whitewash, maple, cherry, walnut
Classic cabinet style	French provincial curves on sides and ends

GUARANTEES:

Structural guarantee	5 years structure and foam
Vinyl	Guaranteed to arrive in good condition
Foot Spa	1 year

WEIGHTS:

Weight	132 lbs.
Shipping weight-crated	204 lbs. (58" x 42" x 29")



Golden Ratio Woodworks Inc.

For latest information visit GoldenRatioWoodworks.com